

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 April 2006 (20.04.2006)

PCT

(10) International Publication Number
WO 2006/040732 A1

(51) International Patent Classification:
B62D 21/15 (2006.01) *B60R 27/00* (2006.01)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:
PCT/IB2005/053358

(22) International Filing Date: 12 October 2005 (12.10.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-298673 13 October 2004 (13.10.2004) JP
2005-264095 12 September 2005 (12.09.2005) JP

(71) Applicant (for all designated States except US): NISSAN MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama, Kanagawa 220-8623 (JP).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


Published:
— with international search report

(75) Inventor/Applicant (for US only): FUJIKAWA, Kazutoyo [JP/JP]; 1198, Kamikasuya, Isehara-shi, Kanagawa 259-1141 (JP).

(74) Agents: STEWART, Michael, B. et al.; Rader, Fishman & Grauer PLLC, 39533 Woodward Avenue, Suite 140, Bloomfield Hills, Michigan 48304 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BODY FRAME STRUCTURE FOR AN AUTOMOTIVE VEHICLE



(57) Abstract: In a body frame structure for an automotive vehicle, the amount of the bending and deforming of a longitudinal frame member (2) in the rear direction can be controlled and the amount of the collision energy absorption during a frontal collision can be increased. A kick-up portion (K) that bends and deforms the front portion (2F) upwardly during the application of the collision load is provided between a front portion (2F) and a rear portion (2R) of the closed section of the longitudinal frame member (2), which extend in the longitudinal direction of the vehicle. A deformation guide member (10), which constrains the longitudinal frame member (2) to bend and deform in the lateral direction of the vehicle at the front portion (2F) by colliding portions of the deformation guide member (10) with each other due to the applied frontal collision load, is provided inside the closed section of the kick-up portion (K) of the longitudinal frame members (2).

WO 2006/040732 A1